


HiFi ENGINE®

For more Hi-Fi manuals and set-up information
please visit www.hifiengine.com



FS 122U12
(FS 122J13)

TO PB-1185

SIGNAL STRENGTH LED
STEREO IND. LED

75 ohm E 75 ohm 300 ohm

BALLUN
ANT. TERMINAL UNIT

PB-1185A

PB-1183

MUTING THRESHOLD LEVEL CONTROL

NARROW MONO ON ON OFF

WIDE STEREO OFF OFF ON

IF WIDTH MONO TEST TONE MULTI PATH MUTING QUARTZ BRAKE SW SW SW SW SW SW

OUT PUT

FIX VAL

- Q401 Q402 Q405 2SC461B
- Q403 TC4020P
- Q404 MC7805CT(NJM78L-05A)
- Q406 HD74S00 A
- Q407 Q408 2SK55D
- Q409 Q410 2SC535B
- Q411 NJM4558DD
- Q412 Q413 Q414 Q418
- Q419 Q420 Q421 2SC1345
- Q415 Q417 Q421 Q422
- Q451 2SA836
- Q416 2SK40

PB 1184A

PB-1151

- NOTES
- 1 ALL RESISTORS IN OHM K 10³ M10⁶
 - 2 ALL CAPACITORS IN MICRO FARADS P10¹² FAR.
 - 3 TRANSISTORS AND DIODES MAY BE REPLACED WITH ANY TYPES HAVING COMPARABLE RATINGS.
 - 4 VOLTAGES MEASURED WITH "VTMM" WITH NO SIGNAL IN PUT.

Due to continued research for improvements, LUX reserves the right to alter the circuit and specifications without notice.

ULTIMATE HIGH FIDELITY STEREO COMPONENT
ACCUTOUCH QUARTZ LOCKED FM TUNNER

T-12